



MC-02DG-22

Have innovation with us

PE Compound

Product Description

MC-02DG-22 has a good mechanical and rheological properties, this grade is suitable for blow-molding applications. this product is in pellet form with white color.

Applications: Blow molding

Product characteristics

Features Good processability, Good mechanical properties

Typical Properties	Method	Unit	Value
Physical			
Melt flow rate (MFI) (190 °C, 5 Kg)	ISO 1133	g/10min	1.3 ± 0.1
Density	ISO 1183	g/cm ³	1.05 ± 0.01
Ash content(600 °C, 30min)	ISO 3451-1	%	15 ± 1
Mechanical			
Tensile strength at yield	ISO 527	N/mm ²	28± 2
Elongation at yield	ISO 527	%	7 ± 1
Flexural modulus	ISO 178	N/mm ²	1200 ± 50
Izod impact strength (notched @23 °C)	ISO 180	KJ/ m ²	45 ± 3
Hardness shore D	ISO 868	points	64 ± 1

Note: Typical properties; not to be construed as specifications

Marun Pooya Polymer Compound Co., NO.2,17th St, Hasan Seif Ave., Sanat Sq., Shahrak e Gharb, Tehran
1466883855, Iran

Email: crm@mppc-co.com Tel: [+982186759092](tel:+982186759092) Fax: +982186759091

Code: PRE/FO/009/0